

## Stratasys J55

The Stratasys J55™ 3D printer combines the quality of Stratasys PolyJet technology with a compact, office-friendly design.

The five material channel, full color printer features a rotating build platform with fixed print head for outstanding surface finish and print quality. Engineered for the office or design studio environment, it features a small footprint and ProAero<sup>TM</sup> filtration technology for odor free, silent and low power operation.

The J55 offers a streamlined design-to-print workflow powered by GrabCAD Print™. This allows users to import their designs using native CAD files or 3MF file formats. GrabCAD Print also enables Pantone® validated color matching. Remote monitoring lets you easily manage your print jobs from outside the office. Additionally, hands-free soluble support removal makes post processing simple and enables the creation of complex parts without compromising accuracy or detail.

Product Specifications	
Model Materials	■ VeroCyanV <sup>TM</sup> ■ VeroMagentaV <sup>TM</sup> □ VeroYellowV <sup>TM</sup> □ VeroPureWhite <sup>TM</sup> ■ VeroBlackPlus <sup>TM</sup> □ VeroClear <sup>TM</sup> ■ DraftGrey <sup>TM</sup>
Support Materials	SUP710™
Build Size/Printing Area	Up to 1,174 cm <sup>2</sup>
Layer Thickness	Horizontal build layers down to 18 microns (0.0007 in.)
Network Connectivity	LAN - TCP/IP
System Size and Weight	651 x 661 x 1551mm (25.63 x 26.02 x 61.06 in.); 228 kg (503 lbs.)
Operating Conditions	Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)
Power Requirements	100-120 VAC, 50-60 Hz, 6A, 1 phase
	220-240 VAC, 50-60 Hz, 3A, 1 phase
Regulatory Compliance	CE, FCC, EAC
Software	GrabCAD Print
Build Modes	High Quality Speed (HQS) - 18.75µm
Accuracy	Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm – ±150µ; above 100 mm – ±0.15% of part length.**  Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm – ±180µ; above 100 mm – ±0.2% of part length.**
	2000 5 0.20. and 100 mm. 1700g, above 100 mm. 20.270 of part longth.

<sup>\*\*</sup>Measured when ambient temperature is 23 °C and relative humidity is 50%.

## **Stratasys Headquarters**

7665 Commerce Way, Eden Prairie, MN 55344

- +1 800 801 6491 (US Toll Free)
- +1 952 937-3000 (Intl)
- +1 952 937-0070 (Fax)

PO Box 2496 Rehovot 76124, Israel

## stratasys.com

ISO 9001:2015 Certified

1 Holtzman St., Science Park, +972 74 745 4000 +972 74 745 5000 (Fax)

